



INDIAN INSTITUTE OF MANAGEMENT SHILLONG
UMSAWLI, SHILLONG: 793018
MEGHALAYA

Phone No: 0364-2308000

www.iimshillong.ac.in

ENQUIRY NO: IIMS/S&P/NIQ/24-25/012

Dated: 01 July 2024

Sub: Notice Inviting Quotations for Supply Installation Testing and Commissioning of AV Equipment's

Offers are invited on behalf of Director, IIM Shillong from registered/ reputed dealer, supplier for tentative requirement of items in sealed cover addressed to the Director, IIM Shillong, Umsawli, Shillong-793018 with the words “ **Quotations for Supply Installation Testing and Commissioning of AV Equipments**”, Enquiry No. with due date boldly superscribed on the top of the envelope and the offer be sent by registered cover/ speed post/ dropped in and must reach to The Stores and Purchase Officer, Indian Institute of Management Shillong, Umsawli, Shillong 793018 latest by 10 July 2024 by 12:00 noon.

(Detailed Description)

SITC of AV Equipment's					
Sl. No.	Items	Quantity	Unit	Rate (Incl. of GST)	Total (Incl. of GST)
1	Active 1000 watt 10” Speaker System (As per specifications in Annexure I)	4	Nos.		
2	4 Channel Compact Analogue Mixer with Bluetooth, USB	2	Nos.		
3	TV Wall mount for upto 65 inch TV	2	Nos.		
4	Active 350 Watt 10” Speaker	2	Nos.		
5	Installation and Commissioning	1	Job		
Total Rs (Incl. of GST)					

The above mentioned rates is inclusive of all taxes

Terms and Conditions:

1. No counter proposal is acceptable and conditional/late quotes are liable to be rejected.
2. **Vendors/Suppliers are required to submit copies of GST Registration, PAN, and copies of work orders of similar works carried out in the quote.**
3. The Institute shall have the right to reject any tender without assigning any reason thereof. No correspondence will be entertained in this regard. Only one best quality item (according to our specification) should be quoted against the item.
4. Technical Brochures of item offered is to be submitted along with quotation
5. Bidders will require to provide samples of the above items when asked for by the Institute.
6. Validity of quoted rates is for a period of 60 days.
7. Stores will be accepted subject to the verification and inspection by the competent authority.
8. Time schedule of delivery is within **30 days** of receipt of supply order or else deduction on gross bill @0.5% per week or part thereof will be made as liquidated damages/ delay in supply subject to maximum of 10% of the value of the delayed supplies.
9. Quoted price should include all other necessary expenses like carriage, insurance, transportation and delivery, Installation, Testing and Commissioning and training to designated staff on how to operate the drone.
10. Warranty on the product should be for a minimum period of 1 year
11. Insurance during transit to be borne by the Vendor/ Supplier/Contractor inclusive of handling within the Institute premises till the completion of final Inspection and acceptance.
12. Bills should be submitted in quadruplicate along with a receipted copy of challan duly endorsed in the desk of the of the Receiving section of the Institute.
13. Payment of the approved vendor for supply of items at IIM Shillong shall be made through cheque or electronic clearing system. In case of cheque, the same will be dispatched registered post and postal charges shall be deducted from their bills. No advance payment will be made.
14. The Institute reserves the right to reject any tender or all tender without any reason.

15. Director, IIM Shillong or his authorized representatives shall be the final authority in setting all disputes and decision will be binding on all concerned.

Sd/-
Stores and Purchase Officer
IIM Shillong

Technical Specification

A. Active 1000 watt 10” Speaker System

Active 1,000 Watt 10" PA Speaker System with DSP and 2-Channel Mixer

Product Features

Show less ▲

- High-Power 1,000-Watt 2-way PA sound reinforcement speaker system for live and playback applications
- Ultra-compact and lightweight system delivers excellent sound even at extreme sound pressure levels
- Dedicated DSP function for EQ, system control and speaker protection and Built-in Bluetooth receiver
- 2-channel mixer with individual Mic/Line inputs and level controls
- Revolutionary Class-D amplifier technology: enormous power, incredible sonic performance and super-light weight
- Extremely powerful 10" long-excursion driver provides incredibly deep bass and acoustic power
- High-performance DSP functions with optimization for 4 unique sound programs: Music, Live, Speech, DJ/CLUB
- Excellent Low-Cut filter performance, switchable at 80, 100, 120 or 150 Hz
- State-of-the-art 1.35" compression driver for exceptional high-frequency reproduction
- Ultra-wide dispersion, large-format exponential horn
- Additional Line output allows linking of additional speaker systems
- Versatile trapezoidal enclosure design allows different positioning Stand mounting with 35-mm pole socket, Tilts on its side for use as a floor monitor
- Ergonomically shaped handles for easy carrying and setup
- High-quality components and exceptionally rugged construction ensure long life

B. 4 Channel Compact Analogue Mixer with Bluetooth, USB

4 Channel Compact Analogue Mixing Frame with FX

Technical Specifications

Number of Input Channels	2 Mono + 1 Stereo Channels, Media Player with USB / BT input
Number of Output Channels	Master L+R XLR Output, Mono-r & Headphone Outputs
Oliver FX	Single FX Engine
Recording	2-Track Recording In/Out
Auxes	1
Frequency Response	20Hz - 30KHz 0.5dB
Max. Input Level	Mic +24dBu, Line +24dBu, Other +20dBu
Max. Output Level	XLR +26dBu, TRS +20dBu
Max Input Power	5 Watts
Faders	60mm

General Specifications

Enclosure	Rugged ABS Housing, IP 43
Knobs	Coloured ABS Knobs
Finish	Charcoal Slate Finish
Mounting System	Desktop Devices with Anti-Skid Rubber Feet
Height	10.8"
Width	2.6"
Depth	6.5"
Weight	1.45 Kgs

C. TV Wall mount for upto 65 inch TV

SPECIFICATIONS

Product Category:	Full-motion TV Wall Mount
Rank:	Economy
Material:	Steel
Metal Sheet Thickness:	Bracket Arm THK=1.5mm cold-rolled sheet,VESA Panel THK=1.8mm cold-rolled sheet,Wall Plate THK=2mm cold-rolled sheet (Bracket Arm THK=0.059" cold-rolled sheet,VESA Panel THK=0.071" cold-rolled sheet,Wall Plate THK=0.079" cold-rolled sheet)
Pipe Size:	30x20x1.5mm Square Steel Tube (1.2"x0.79"x0.059" Square Steel Tube)
Surface Finish:	Powder Coating
Color:	Fine Texture Black
Dimensions:	468x475x420mm (18.4"x18.7"x16.5")
Fit Screen Size:	32"-70"
Fit Curved TV:	Yes
Mounting Hole Pattern:	VESA & Universal
VESA Compatible:	75x75,100x100,100x150,150x100,100x200,200x100,150x150,200x200,300x200,400x200,300x300,400x300,400x400
Max. Mounting Hole:	400x400
Weight Capacity:	40kg (88lbs)
Strength Tested:	2 Times Approved

Profile:	62~468mm (2.4"~18.4")
Tilt Range:	+5°~15°
Swivel Range:	+60°~60°
Screen Level:	+3°~3°
Screen Freely Tilting:	No
Installation:	Solid Wall,Double Stud(406mm/450mm)
Panel Type:	Detachable Panel
Wall Plate Type:	Fixed Wall Plate
AV Component Shelf:	No
Direction Indicator:	Yes
Cable Management:	Yes
Anti-theft:	No
Bubble Level:	No
Accessory Kit Package:	Normal/Ziplock Polybag,Compartment Polybag

D. Active 350 Watt 10" Speaker

Active 350-Watt 10" PA Speaker System with Built-in Media Player, Bluetooth Receiver and Integrated Mixer

Product Features

[Show less](#)

- High-Power 350-Watt 2-way PA sound reinforcement speaker system for live and playback applications
- Ultra-compact and lightweight system delivers excellent sound even at extreme sound pressure levels
- Built-in media player with display, SD card slot, USB port and Bluetooth receiver
- 2-channel mixer with individual Mic/Line inputs, Volume controls and Clip LEDs
- Dedicated 2-band EQ plus integrated sound processor for ultimate system control and speaker protection
- Extremely powerful 10" long-excursion driver provides incredibly deep bass and acoustic power
- State-of-the-art 1" compression driver for exceptional high-frequency reproduction
- Ultra-wide dispersion, large-format exponential horn
- Additional Line output allows linking of additional speaker systems
- Ergonomically shaped handles for easy carrying and setup
- High-quality components and exceptionally rugged construction ensure long life